



Staff Loudspeaker Unit

STS-SU1-G / STS-SU1-B /
STS-SU1-SS

Our free-standing combined speaker and directional microphone module for the staff side has an integral loudspeaker, microphone with a semi-rigid stem, adjustable neck and mute switch.

Physical Data

| | |
|--------------|---|
| Dimensions | Height – 370mm (6.30") Width – 95mm (2.76") Depth – 150mm (3.94") |
| Weight | 820g (1.80lbs) |
| Construction | Stainless Steel |
| | Mild Steel |
| Finish | Grey Powder Coated Leatherette |
| | Black Textured Powder Coated |
| | Brushed Stainless Steel |

Technical Data

| | | |
|------------|----------------------|-----------------------------------|
| Speaker | RMS | 5W |
| | Impedance | 4Ω |
| | Output | SPL 1W @ 1M 85dB |
| | Frequency Response | 150Hz - 10300Hz |
| Microphone | Directional Response | Cardioid |
| | Frequency Response | 150Hz - 10500Hz |
| | Sensitivity | 49.5dB+ 2dB @ 1kHz (0dB=1V/pa) |
| | Impedance | 1.6K Ohms+ 3-% @ 1kHz |

Applications

For use where one to one communication takes place at a counter or booth with a security screen:

- Banks
- Post Offices
- Ticket Kiosks
- Information Centres
- Airports

Standards

- CE, ROHS and WEEE compliant



Talk to us now:
+44 (0) 1732 223900 (UK & ROW)
+1 616 392 3400 (US & Canada)
www.contacta.co.uk