



V14 Hearing Loop Driver

V14-UK / V14-EU /
V14-AUS / V14-USJ

Our highly efficient and compact V14 is a constant current, single output hearing loop driver, suitable for medium-sized facilities and venues.

It has a Class-D amplifier output stage and an audio subsystem built around an advanced DSP core. Combined with a powerful CPU to ensure peak performance, the V14 uses cutting edge technology proven in the pro audio world to achieve life-like speech and first-class music reproduction.

Features

- DSP controlled automatic gain control and high frequency compensation for metal loss
- Class-D amplifier output stage capable of delivering $5A_{RMS}$ @ $>14V_{RMS}$
- Ultra-efficient power utilisation (up to 90% efficient)
- True constant current output stage
- Simple user interface
- Backlit LCD display
- Sleep mode
- Continuous self-testing
- Integrated protection circuits with temperature, voltage, short circuit and DC detection
- Compact half-width 1U chassis (compatible 6U Rack Cabinet available upon request)

Components

- V14 Hearing Loop Driver
- PS-60 Power Supply

Applications

Suitable for medium sized facilities, such as:

- Meeting rooms
- Classrooms
- Care & nursing rooms
- Waiting rooms
- Lecture halls

Voltage and Current

- $>14 VRMS$ @ $5A RMS$

Standards

- BS EN 55103-1: 2009 (EMC emissions)
- BS EN 55103-2: 2009 (EMC immunity)
- FCC class "B" EMC (emissions)
- ICES-003
- IEC 60118-4 (in correct installations)
- IEC 62489-1

Accessories

- Single V-Series Mounting Bracket [MBR-V1]
- Dual V-Series Mounting Shelf [MBR-V2]
- Blanking Plate for Dual V-Series Mounting Shelf [MBR-VBLANK]
- 6U Rack Cabinet [IL-AC-RACK-19]

Talk to us now:
+44 (0) 1732 223900 (UK & ROW)
+1 616 392 3400 (US & Canada)
www.contacta.co.uk



Physical Data

Dimensions	Height – 42mm (1.65") Width – 196mm (7.80") Depth – 132mm (5.20") [150mm (5.90") incl. XLR and control dial]
Weight	938g (2.06lbs)
Construction	Mild Steel
Finish	Black Powder Coated

contacta 

Technical Data

Power Supply	100W 24Vdc 4.17A via External PSU (PS-60) Class 6 External PSU (100V-240V AC 50Hz-60Hz)	
Inputs	1 X Balanced Line Level (3 Pin Euro-Block) or 1 X Balanced Line Level (XLR) [optimised for -10dBV to 0dBv]	
	1 X Mic Level (12V phantom power via 680Ω) [optimised for levels above -45dBv]	
	1 X DC Input	
Outputs	1 X Loop Output (5.08mm Euro-Block)	
Loop Output Characteristics	Voltage	14Vrms (33.94Vpk-pk) @ 5Arms (14.14Apk-pk)*
	Current	5Arms (14.14Apk-pk) up to 300 seconds*
	Loop Connector	5.08mm Euro-block
Audio System	Frequency Response	80Hz to 6.5kHz
	Distortion	THD+N <1% (-40dB)
	AGC	Peak detecting
	HF Comp	7 optimised stages
Display & Controls	Display	LED Backlit LCD display
	Control	Single rotary control
Fault Monitoring and Protection	Main Display	Open circuit loop (DCR measurement)
		Loop ground fault
	Front Panel LED	Output voltage clipping
	Cooling	Internal heatsink with thermal protection

*Note 1: Z=2.8Ω (214.7uH +1.27Ω @ 1.6kHz), Note 2: 1% (-40dB) distortion)

Rear Connections



Talk to us now: +44 (0) 1732 223900 (UK & ROW)
+1 616 392 3400 (US & Canada)
www.contacta.co.uk