



Radio Frequency Stationary Transmitter 865MHz/915MHz

The Radio Frequency Stationary Transmitter is intended for rack mounting, available using 865MHz (UK/EU) or 915MHz (USA/AU) frequencies. It uses internationally compatible frequencies to transfer clear sound to portable receivers [RF-RX1-865/915].

It is designed to provide wireless and amplified assistive listening in large venues from a source to compatible RF receivers using FM radio waves.

Key Features

- Improved range using adjustable low/high power setting
- Digital audio transmission technology
- Excellent sound quality - frequency bandwidth 70Hz~12kHz suitable for both speech and music
- Inbound Bluetooth™ streaming
- 42 selectable channels
- OLED display with easy to use settings menu
- Auto-Lock for selected channel
- Improved audio connectivity including Phantom Power and balanced connections
- Exclusive software suite for fast group programming via smart chargers

contacta

RF-TXRM-865 / RF-TXRM-915

Applications

Wireless assistive listening in large venues for multiple recipients, using compatible personal receivers [RF-RX1-865/915] with a variety of listening options.

- Lecture Halls
- Auditoriums
- Meeting Rooms
- Conferences
- Places of Worship

What's in the Box

- Radio Frequency Stationary Transmitter 865MHz/915MHz [RF-TXRM-865/915]
- Power Supply Adaptor [UK-EU-865, US-AU-915]
- 19" Rack Mount Bracket
- Earth (Ground) Cable for Optional Use
- Fixing Screws
- TNC Rod Antenna

Compatible Accessories

- Portable Radio Frequency Receiver [RF-RX1-865/915]

Talk to us now:
+44 (0) 1732 223900 (UK & ROW)
+1 616 392 3400 (US & Canada)
www.contacta.co.uk



Physical Data

Dimensions	Height – 51mm (2") Width – 215mm (8.46") Depth – 210mm (8.26")
Weight	1.25kg (2.75lbs)
Finish	Mixed

contacta 

Technical Data

Carrier Frequency Range	865MHz (UK/EU) / 915MHz (USA/AU) (country dependent)
RF Output Power	Hi: 18 dBm Mid: 13 dBm (country dependant) Lo: 10 dBm
Antenna	TNC connector
Headphone Output	200mW @ 32 ohm
Inputs	Mic in: 3.5mm & 6.3mm Aux in: RCA Loop in: 6.3mm Incoming Bluetooth™ streaming
Mic/Line Inputs	Mic Input Limits: -30dBv Line Input Limits: 10dBv Unbalanced/Balanced connections available
XLR Connector	Level= \-30d Bv Balanced Connection
Mic-In Connectors	Mono/Stereo Aux out= Mono Mic Level=-30dBv
Connectors	AUX IN = Audio Source MICIN = Dynamic Mics PH PWR = Electret Mics
Outputs	Earmic out: 3.5mm, stereo Aux out: RCA Loop out: 6.3mm
Wireless Coverage	Approx. 100 metres (line of sight @ Hi power)
Power Requirements	100 ~ 240 V AC / 12 V DC; 1A switching power
Frequency Response	70Hz – 12kHz
Channel	42 simultaneous groups
Display	Backlit OLED
Software	Smart programming software [OKAY-CON-SW] for fast setup of multiple receivers

Front / Rear Panels

